



## Product Data Sheet

### JMR-800

<b>Description:</b>	A 200-micron mirror finish top coated metallised polyester film with an aggressive, permanent solvent based acrylic pressure sensitive adhesive. The product has been top coated to improve ink adhesion for flexographic, offset, letterpress and screen-printing.
<b>Application:</b>	These products are intended for use as high quality markings requiring metallic luster, durability and dimensional stability e.g. custom product identification markings, quality nameplates, fleet markings, etc.
<b>Dimensional Stability:</b>	Excellent. No measurable shrinkage on applied parts.
<b>Minimum Application Temperature:</b>	10°C
<b>Service Temperature Range:</b>	-45°C to 130°C
<b>Opacity:</b>	JMR will completely hide black legend upon application.
<b>Expected Exterior Life:</b>	3 years.
<b>Water Resistance:</b>	Excellent. Test piece aged 24 hours after application to Stainless Steel panel before testing. Not affected when immersed in 22°C water for seven days.
<b>Humidity Resistance:</b>	Excellent.
<b>Solvent Resistance:</b>	Good resistance to most petroleum based solvents. For ultimate solvent resistance, edge sealing is recommended.
<b>Abrasion Resistance:</b>	Excellent.

JMR-800



Supplied by: Halifax Vogel Group in Australia and New Zealand  
Customer Service P: 1300 558 882 (Australia Wide) +61 (02) 9556 6000 (outside Australia)  
SYDNEY (Head Office) \* MELBOURNE \* BRISBANE \* PERTH \* ADELAIDE \* AUCKLAND

[www.halifaxvogel.com.au](http://www.halifaxvogel.com.au)

**Product Performance and Suitability:** All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitute a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorized to give any warranty, guarantee or make any representation in addition or contrary to the above.