



Product Data Sheet

MM200GTC

Description:	A topcoated metallised gold polyester film coated with a permanent solvent based acrylic adhesive and backed with a two sided poly coated lay flat release liner.		
Application:	This product is UL * & CSA recognised for indoor/outdoor use. For printing of high quality labels and decals requiring a metallic luster, or for labeling of electrical appliances where UL/CSA recognition is required.		
Physical Properties:	Thickness:	Film:	51 microns
		Adhesive:	25-28 microns
		Liner:	170 microns
Dimensional Stability %:	No shrinkage observed on Aluminium panel 70°C for 24 hours		
Adhesion Properties:	<i>Adhesion from:</i>	<i>Average (N/m)</i>	<i>Expected range (N/m)</i>
	Glass	682	550-825
	Acrylic	627	495-770
	Stainless Steel	726	505-380
	Expected Shear (hours)	25	
	Tack (gm/sq cm)	125	50-400
Exterior Life:	2-3 Years		
Application Temperature:	Minimum 10°C		
Service Temperature	-40°C to 150°C		
Shelf Life:	2 years when stored at 21°C and 50% relative humidity		

MM200GTC



Supplied by: Halifax Vogel Group in Australia and New Zealand
Customer Service P: 1300 558 882 (Australia Wide) +61 (02) 9556 6000 (outside Australia)
SYDNEY (Head Office) * MELBOURNE * BRISBANE * PERTH * ADELAIDE * AUCKLAND

www.halifaxvogel.com.au

Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitute a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorized to give any warranty, guarantee or make any representation in addition or contrary to the above.